
DRACAST

LED500 X-SFRIFS

The X Series is the newest generation of LED panel lights from Dracast. The X-Series is designed with portability in mind, with each model weighing just a few pounds. The panel includes an installed mounting yoke with a 5/8" baby pin receiver for fast and easy mounting on compatible light stands or suspension clamps.

The X Series is available in three versions: 5600K, 2800K - 8000K Variable CCT, and 2800K - 8000K Variable CCT PLUS full spectrum RGB. X-Series panels are also available in two sizes: LED500 (35W) and LED1000 (70W). All X-Series sizes and variations are compatible with the Dracast DRX app for iOS and Android. X-Series lights feature dual NP-F battery plates for optional battery power on the go.

Also included are preset color gels and filters, as well as a collection of customizable effects and presets (RGB models). The light can be fully controlled manually via the user-friendly control panel on the back of the fixture, or by using Dracast DRX. Using the DRX companion app, all of the features of the light can be easily controlled along with the added ability to control multiple X-Series lights simultaneously.



Photometric Data		3 ft / 0.9 m	6 ft / 1.8 m	9 ft / 2.7 m	12 ft / 3.6 m
X-SERIES LED500 5600K DRX500DN		87.05 fc	24.80 fc	11.89 fc	7.15 fc
		937 lux	267 lux	128 lux	77 lux
X-SERIES LED500 3200K - 5600K DRX500BN		66.33 fc @ 2800K	20.07 fc @ 2800K	10.22 fc @ 2800K	6.13 fc @ 2800K
		77.67 fc @ 5600K	23.69 fc @ 5600K	12.08 fc @ 5600K	7.25 fc @ 5600K
		78.50 fc @ 8000K	24.06 fc @ 8000K	12.17 fc @ 8000K	7.34 fc @ 8000K
		714 lux @ 2800K	216 lux @ 2800K	110 lux @ 2800K	66 lux @ 2800K
		836 lux @ 5600K	255 lux @ 5600K	130 lux @ 5600K	78 lux @ 5600K
		845 lux @ 8000K	259 lux @ 8000K	131 lux @ 8000K	79 lux @ 8000K
X-SERIES LED500 2800K - 8000K PLUS FULL SPECTRUM RGB DRX500RGB		77.29 fc @ 2800K	22.39 fc @ 2800K	10.87 fc @ 2800K	6.50 fc @ 2800K
		85.84 fc @ 5600K	24.71 fc @ 5600K	12.08 fc @ 5600K	7.15 fc @ 5600K
		91.79 fc @ 8000K	26.20 fc @ 8000K	12.91 fc @ 8000K	7.71 fc @ 8000K
		832 lux @ 2800K	241 lux @ 2800K	117 lux @ 2800K	70 lux @ 2800K
		924 lux @ 5600K	266 lux @ 5600K	130 lux @ 5600K	77 lux @ 5600K
		988 lux @ 8000K	282 lux @ 8000K	139 lux @ 8000K	83 lux @ 8000K
Part No.	Included				
DRX500DN	LED500 X-Series 560	00K Light, Aluminum 5/8" Baby Pi	n Yoke, Nylon Clam Shell Case,	12V A/C Power Supply, NP-F Mo	ount Battery Plate
DRX500BN	LED500 X-Series Bicolor Light, Aluminum 5/8" Baby Pin Yoke, Nylon Clam Shell Case, 12V A/C Power Supply, NP-F Mount Battery Plate				
DRX500RGB	LED500 X-Series Bicolor + RGB Light, Aluminum 5/8" Baby Pin Yoke, Nylon Clam Shell Case, 12V A/C Power Supply, NP-F Mount Battery Plate				

Product Information Sheet

DRACAST

FIXTURE WEIGHT: 3.07 LBS (1.39 KG) PACKAGED WEIGHT: 4.7 LBS (2.13 KG)







Specifications	Details		
Optical System	256 SMD LED chips in 16x 16 arrangement.		
Light Aperture	8 x 8 inches (203mm x 203mm)		

Light Aperture	8 x 8 inches (203mm x 203mm)
Beam Angle	45 degrees
Weight	3 lbs (1.36 kg)
Handling	Aluminum Yoke, Dual Locking Tilt Control
Mounting	Baby 5/8" Pin
Tilt Angle	+/- 180 degrees
Voltage Input	12 V DC
Power Consumption	35 W
Power Connection	Barrel connector, 100 - 240 VAC, 50 - 60 Hz, 4.0 A
Battery Connection	Dual NPF Battery Plate (included)
Battery DC Voltage	7.4V * 2 DC
Battery Light Output	100% of Total Output
Color Temperature	3200K - 5600K (Variable or fixed color temperature depending on model)
Color Rendition	CRI > 96
Dimming	0% - 100% Continuous
Controls	Local On-Board Manual Controls, App Control, Group Master / Slave Control
Housing Color	Anodized Blue / Black

Available Accessories

Aluminum / Plastic

50,000 hours

Housing Build

Est. LED Lifetime

BDDRX500	Dracast Barndoors for X-Series 500
BDSBX500	Dracast Softbox for X-Series 500
DRLSCLS	Dracast Compact Portable Light Stand
DRBKNPF6000D	Dracast NP-F Battery Kit - x2 6600 mah batteries x1 digital NP-F charger
DB0068	DCB Element 7975F Waterproof Utility Case with Foam Insert
DRKITBAG	Dracast Nylon Padded Travel Case

