



| | | | | |
|--|------------|--|-----------|-----------|
| 1" 2.4/4.7mm C | | 1" | 2/3" | 1/1.8" |
| FOCAL LENGTH | | f=4.7mm | | |
| MAX. DIAMETER (RATIO) | | F=1:2.4~11 | | |
| ELEMENT | | 11 GROUPS 15 ELEMENTS | | |
| PICTURE SIZE | | 9.6x12.8mm | 6.6x8.8mm | 5.4x7.2mm |
| ANGLE | VER. ANGLE | 95.4° | 72.2° | 60.8° |
| | HOR. ANGLE | 112.2° | 90.0° | 77.4° |
| | DIA. ANGLE | 123.0° | 103.7° | 91.4° |
| DISTORTION (TV) | | -0.58% | | |
| SHOOTING RANGE AT MINIMUM FOCUS DISTANCE | VER. | 272.1mm | 178.8mm | 143.6mm |
| | HOR. | 375.6mm | 246.6mm | 196.8mm |
| | DIA. | 480.5mm | 317.3mm | 253.0mm |
| MINIMUM FOCUS DISTANCE | | 0.1m | | |
| FLANGE BACK | | 17.526mm in air | | |
| BACK FOCUS | | 9.0mm in air | | |
| FILTER SCREW SIZE | | - | | |
| FRONT/REAR EFFECTIVE DIA. | | FRONT ϕ 60.5mm REAR ϕ 14.8mm | | |
| MOUNT | | C-MOUNT | | |
| EXIT PUPIL | | -128.6mm | | |
| TEMPERATURE RANGE | | -10~+50°C | | |
| STORAGE TEMPERATURE RANGE | | -20~+60°C | | |
| RESOLUTION CENTER/CORNER | | CENTER 100lp/mm CORNER 50lp/mm | | |
| LENS COATING | | WIDE BAND MULTI COATING | | |
| WEIGHT | | 360g | | |

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



| | | | | | |
|------------|---------|-----|-----------------|------|---------|
| | | 尺度 | 1/1 | 工場番号 | S10-569 |
| | | 機種名 | 1" F2.4 f=4.7mm | | |
| 2020.02.10 | #114 変更 | 機種番 | LM4HC 外観図 | | |
| 2019.07.07 | 作成年月日 | | | | |