


Product Brochure



Zixi Feeder Edge Point

- Communicates with Zixi Receiver or with Zixi Broadcaster platform using UDP-based, video-optimized protocols on standard IP networks, including the public Internet
- Accepts input from a broad range of hardware/software encoders and professional-grade cameras
- Mediates between video devices and the Internet, ensuring quality and deliverability
- Easy-to-use graphical administration interface


- Provides management and control of video transport at the source
- Removes distance as a consideration for video transport
- Allows content producers to redesign workflows based on immediate availability of content



Zixi Receiver Edge Point

- Accepts input from Zixi Feeder or Broadcaster via standard IP networks (including the public Internet)
- Outputs professional-quality video to a broad range of Integrated Receiver-Decoders (IRDs), and to file system
- Zixi Receiver software runs on standard PC hardware, lowering costs and facilitating simple integration into the network

- Guaranteed delivery of video with the quality originally specified at the entry point
- Elimination of distance as a factor in production
- Ability to distribute live content to multiple sites with low latency



Zixi Eco-Zystem:

The Zixi Eco-Zystem is a growing list of partners who have added support for Zixi Feeder into their encoders, cameras, and software apps.

- Because Zixi is a software solution, integrating Zixi feeder is simple and easy to do.
- The Zixi SDK and accompanying API enable any hardware or software vendor to seamlessly integrate Zixi enabling them to offer a reliable, secure IP delivery option to their customers.
- The Zixi Feeder edge point sits at the content acquisition side and wraps the encoded file in the Zixi Transport Stream and initiates the contribution process.
- Zixi Feeder can run on iOS and Android devices, and is tested with a variety of different processors. Zixi Feeder can also be deployed on a Zixi Server running side by side with a non-Zixi enabled camera, encoder, or software toolset.
- Zixi Feeder can accept MPEG TS or RTP, RTMP, and ASI.



Zixi Edge Point Configurations

- Zixi Feeder Edge Point devices (embedded and non) can be configured to communicate directly with a Zixi Receiver Edge point sending a Zixi transport stream point to point over any distance using a standard internet connections.
- A Zixi Feeder Edge Point can also be configured to send a Zixi Transport stream to the Zixi Broadcaster Platform where it can be managed, modified, and distributed to Zixi Receiver Edge Point enabled devices and non-Zixi Edge Point devices alike.
- With the Zixi platform, content can come from anywhere and can be delivered to any device, anywhere, at any time.

The Zixi Eco-Zystem®

ateme

ADTEC
Digital

Blonder
Tongue

BrightSign®

harmonic

JVC

NewTek

nano
COSMOS

Open Broadcast Systems

TERADEK


THOMSON
VIDEO NETWORKS

VITEC
VIDEO INNOVATIONS

telestream

Zixi Edge Point Applications:

- Zixi is running in a variety of different production workflows ranging from sports and Electronic News Gathering workflows, satellite backup, contribution and first mile ingest, Live Event production, and more.
- Live feed - JVC has integrated Zixi directly into its broadcast camera line up enabling Zixi streaming directly from their camera over 4G/LTE or Ethernet through a USB dongle to either the Zixi Broadcaster Platform (On Premise or in the Cloud) or direct to a Zixi Receiver or Zixi Receiver enabled device.
- Increased efficiency – Zixi speed up ENG workflows by requiring fewer people and less equipment to produce a field or in studio broadcast, lowering costs without modifying the production workflow.



Zixi Channel Bonding:

- Zixi Feeder Edge Points now support bonding as part of the Feeder package which aggregates bandwidth from multiple connections.
- This enables the delivery of higher bit rate content using the Zixi protocol over managed and unmanaged networks

Zixi LLC

www.zixi.com

+1 877 494 9426



Feeder Specifications

Supported Protocols

Input:

- MPEG-TS over UDP (unicast and/or multicast) and/or RTP
- RTMP
- ASI

Output:

- Zixi protected transport to Zixi Broadcaster
- UDP to specified IP address and port
- MPEG-TS output to filesystem

Quality of Service and Error Correction

Transport protocol used among Zixi Broadcaster and Zixi Receiver optimizes bandwidth to deliver broadcast quality

Maximum stream latency can be specified, which is then guaranteed assuming available bandwidth

FEC maximum overhead can be specified as a percentage of the original bitrate

Content-aware forward error correction

Programmable HTTP/JSON API for monitoring, automation and customization

Performance, Availability, and Security

Stream password protection

Stream encryption with up to 256-bit AES encryption

SMPTE 2022 FEC decoding allows recovery of input streams coming from a managed network

Web administration app for configuration

TR-101-290 MPEG stream analysis (priorities 1 and 2)

SSH secure tunnel access to Zixi Feeder for configuration and management

Remote management: connection to 'My.zixi, cloud management system for zixi servers.


Reliability and Failover

Create output streams from single input

Direct outputs to multiple Zixi Broadcasters, including both cloud-based and self-hosted locations

Demuxing

Support for multi-program transport streams (MPTS): programs may be split into separate single output streams (SPTS).




Zixi Feeder allows precise control of multi-program

Filters may be applied to individual programs to create new output streams with specific elementary IDs

Bonding:

Use multiple connections to aggregate bandwidth

Hitless recovery from complete link drops or congestions



Zixi stream resiliency as compared with traditional protocols

Zixi LLC

www.zixi.com

+1 877 494 9426



Receiver Specifications

Supported protocols

Input:

- Zixi protected transport and/or RTP with SMPTE-2022 support from Zixi Broadcaster located in the cloud and/or on local premises
- MPEG transport stream files from local file system

Output:

- UDP
- Output to compatible ASI cards
- MPEG transport stream output to local file system
- File output segmented by user-selected time interval
- Re-multiplex output streams to strict CBR for extensive compatibility with Integrated Receiver-decoders (IRDs)

Availability and Reliability

Pull streams from multiple Zixi Broadcasters

Ability to assign fallback source to Zixi Receiver output to ensure continuity

Stream monitoring available statistics, throughput, packet rate, FEC, and ARQ measurements

System Management

Web administration app for configuration SSH access via secure tunnel

Remote management: connection to 'My.zixi, cloud management system for Zixi server.

Security

Stream password protection

Decryption of inbound video using up to AES 256-bit encryption

System Requirements

Supported operating systems:

- Windows® Server 2008; Windows Server 2012;
- Windows 7; Windows 8
- CentOS or Red Hat Enterprise Linux 5.x/6.x 32-bit or 64-bit

Recommended processor: Intel® Core™ i3 dual-core or quad-core

Memory requirements: 1GB

Network interface cards: Minimum of two gigabit Ethernet

The 'Stream details' window shows configuration for 'Live-event-stream-1'. It has radio buttons for 'Pull' (selected), 'UDP', and 'File'. Under 'Stream parameters', fields include Host (173.21.44.234), Backup Host (8.3.78.2), Port (2077), Stream (stream1), Password (password), Latency (8000), Local interface (Any), Min. bitrate (0), Decryption type (AES 256), and Decryption key (a 32-character hex string). A 'Cloud' button is next to the Host field. 'Ok' and 'Cancel' buttons are at the bottom right.

Zixi Receiver pulls streams from Zixi Broadcaster

The 'Add output source' window shows 'Source priority' with 'Primary source' and 'Fallback source' radio buttons. A text field contains 'pull: 127.0.0.1:2077/stream2'. 'Add' and 'Cancel' buttons are at the bottom right.